



# QVIS® | 4MP IP BULLET CAMERA

Superior Image quality • Switchable H.264 / H.265



## FEATURES:

- Up to 4 mega pixel high resolution
- Wide dynamic Range
- Privacy masking
- Day and night
- Dual video streams
- Plug and Play with all Qvis NVR's
- 4MP@15FPS
- 3D Digital Noise Reduction
- DC12V & PoE
- IR cut filter
- Onvif 2.4
- IP67 weather-proof protection
- Supports both H.264 and H.265  
H265 Twice the compression  
using half the hard drive storage
- Superior Image quality

## RECOMMENDED NVR:

Click here to find out more



SPECIFICATION		MB-4MP-FW
<b>CAMERA</b>		
Image Sensor	1/3" Progressive Scan CMOS Sensor	
Min illumination	0.05 Lux (F1.2), 0 Lux (IR on)	
Shutter time	Auto, 1/25 ~ 1/10000s	
Lens	3.6mm	
Lens Mount	M12	
Day & Night	IR cut filter with auto switch	
Wide Dynamic Range	>80dB	
Digital noise Reduction	3D NR	
S/N Ratio	≥50db(AGC OFF)	
Privacy Masking	Up to 4 areas	
<b>COMPRESSION STANDARD</b>		
Video Compression	H.264/H.265 & MJPEG	
H.265 code profile	Main Profile	
Video bit rate	32KB ~16Mbps, support VBR, CBR	
Dual Stream	Dual-stream encoding	
<b>VIDEO</b>		
Max Image Resolution	2688 x 1520	
Resolution	2592*1520/2048*1520/1080P(1920×1080)/ D1(704×576)/VGA(640*480)/QVGA(320×240)	
Frame Rate	Main Stream	2592*1520(1~15fps); 2048*1520/1080P(1 ~ 25/30fps)
	Sub Stream	D1/VGA/QVGA(1 ~ 25/30fps)
<b>NETWORK</b>		
Network Storage	Video record, Picture format	
Alarm Trigger	Manual, Automatic (motion detection, alarm, schedule, cycle)	
Protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
Alarm data transmission	FTP, E-mail, Browser, CMS	
System Compatibility	ONVIF 2.4	
<b>INTERFACE</b>		
Communication Interface	1 RJ45 10M/100M Ethernet interface	
<b>GENERAL</b>		
Operating Conditions	-20°C~+55°C , Less than 90% RH	
Power Supply	DC12V / PoE (802.3af)	
Power Consumption	<3W	
Weather Proof	IP67	
IR Range	Up to 30M	
Dimensions	70mmx66mmx160mm	
Weight	0.38Kg	
Max. User Access	8/20 users, IE, Google, Firefox	
Smart Phone	iPhone, iPad, Android	