

61 G=B 9GG F 5B ; 9

VAN-E37-V2W

EXTERNAL 700TVL, EFFIO-E DSP

Armoured Housing Privacy Masking Day & Night ATR High Light Compensation



OSD Menu Back Light Compensation Dual Voltage Dynamic Noise Reduction Intelligent IR



700TVL Professional Vandal Resistant IR Dome CCTV Camera



VAN-E37-V2W SPECIFICATIONS


CCD	1/3" 960H Exview HAD II CCD
DSP	Enhanced Effio-E
TVL	COLOR: 650TVL , B/W: 700TVL
Lens	2.8-12mm Varifocal
IR Range	25-30M
IR Leds	30 PCS
Minimum Illumination	0 Lux (IR ON)
Gamma Correction	0.45
Video Output	1Vp-p,75Ω
Effective Pixels	PAL: 976 (H) × 582 (V) , NTSC: 976 (H) × 494 (V)
Auto Electric Shutter	PAL:1/50-1/100,000S NTSC:1/60-1/100,000S
White Balance	ATW/PUSH/USER1/USER2/ANTI CR/ MANUAL/PUSH LOCK
Back Light Compensation	BLC & HSBLC & ATR (Adaptive Tone Reproduction)
Day/Night	Auto/COLOR / B&W / Infrared LED exposure optimization
Motion Detection	ON/OFF(4 Zone)
Privacy Masking	ON / OFF (8 Marks)
Language	English/Japanese/Chinese/German/ French/Russian/Portuguese/Spanish
IR Range	25-30M
Menu	OSD Control Built-in, Second Video, Baluns
S/N Ratio	52dB (AGC OFF)
Automatic Gain Control	AUTO (4 STEP)
Dynamic Noise Reduction	2D-NR
IP Rating	IP66
Power Supply	DC12V, AC24V, Dual Power Voltage
Scanning System	2:1 Interlace
Current Consumption	105mA (IR OFF) , 345mA (IR ON)
Storage Temperature	-20~+60°C
Operating Temperature	-10~+50°C
Dimensions	Φ145*115mm
Weight	800g



GENERAL FEATURES

- 1/3" Camera (Sony Effio-E)
- Mechanical Focus Adjustment
- Multi-Language OSD Control
- ATR (Adaptive Tone Reproduction)
- High Light Compensation (HLC)
- 2D Noise Reduction
- High Contrast Images
- Ideal for Backlight Environments
- Privacy Mask
- Motion Detection
- Second Video
- OSD Control Built-in

DIAGRAM



DIMENSIONS

145X145X115mm

COLOUR

WHITE

VAN-E37-V2W

EXTERNAL 700TVL, EFFIO-E DSP

2D-DNR



2D-DNR (2-DIMENSIONAL DIGITAL NOISE REDUCTION)

Removes the noise in low intensity illumination environment and reproduces the better and clearer image qualities.

HLC



HLC - HIGH LIGHT COMPENSATION

Detects bright highlights and masks them out in order to reveal detail which would otherwise be obscured by the flare effect from a strong light source, such as a torch light or car headlights.

ATR



ATR - ADAPTIVE TONE REPRODUCTION

ATR improves the visibility of the entire picture by providing the optimum gradation compensation.

INTELLIGENT IR



INTELLIGENT IR


The camera automatically adjust the infrared light required, as the subject moves closer to or further away from the camera, this results in a clear image that is not washed out or too dark.

DUAL POWER 12/24V

3 - Axis Gimble

20mm Conduit Point

Composite Video & Power Terminal Connection



Detachable BNC For 2nd Video Out For Test Monitor

OSD Joystick

Built-in Balun (Terminal Connector)

ADDITIONAL INFORMATION

VANDAL BRACKET



CODE: BK-2000W

Call Us Now!!!



1890 866 900

