

PTZ-TVI-20

20X, 2MP TVI IR PTZ DOME CAMERA

1080P

- Full 1080P Recordings

**Full HD
1080**
**UP TO
150M**
**IR
RANGE**

- 150M IR RANGE

**4/1
IN/OUT**
(“ ”)

- 4 channel input,
1 channel output

**360°
CONTINUOUS**
→

- 360° Pan range

**20X
OPTICAL
ZOOM**


SPECIFICATION:

Manual speed	Pan 0.1°~ 220°/s Tilt 0.1°~ 180°/s
Preset speed	220°/s
Rotation	Pan continuously 360°, tilt 0~90°with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scan
Display zone	8 programmable zones with editable title
Decoder	Built-in
Video output	Female BNC, TVI
Remote controlling	RS485/Telemetry over coax
Baud rate (RS485)	2400/4800/9600/19200 bps
Alarm function	4 channel input, 1 channel output (switch signal)
IR range	150m
IR leds	12pcs
Temperature	Outdoor -10°C+60°C
Humidity	0~95% (non-condensation)
Protection grade	IP66, lightning-proof, surge-proof, wave-proof, all-day defend cover,
Power supply	AC 24V ±4V
Power consumption	Outdoor 50W
Temperature	-10°C+60°C
Gross weight	6.9kg
Camera sensor	1/3" Sony CMOS Sensor
Resolution	1920×1080
Optics	Optical x20, f = 4.7mm ~ 84.6.0mm
Angle	Appr. 55.2° (Wide) to 3.2° (Tele)
Min. Illumination	Color : 0.5 lux, BW : 0.1lux
S/N (Y signal)	52dB
White Balance	Auto
ICR	Manual/Auto
DNR	Auto / Off / Low / Middle / High
HLC	Off / On
Defog	Off / On
Max Gain	Auto
Iris	Auto
Flip	Vertical, Horizontal, Vertical-Horizontal, OFF Selectable

FEATURES:

- 2MP, 1080P Video Output
- 4.7 - 84.6mm Varifocal Lens
- 4 channel input, 1 channel output
- 20X Optional Zoom
- Up to 150M IR Range
- Day & Night
- IP66 Rating
- HLC
- OSD Menu
- AC 24V
- Pan: 360° Continuously
- Tilt down 90°, with auto-flip 180°
- De-fog
- IR-CUT

DIAGRAM:

